

()



•
• ()
•



() :

- **recurrent_type=first**
- **recurrent_type=next**

<https://partner.rficb.ru/alba/input/> 1 2 :

	A PI		/
ord er_id	1. , 6-20. 0, 2.0		123456 (6) (order_id) - (CMS) . . : https://partner.rficb.ru/alba/input/?name=Rent_hall&cost=15200&key=AgI%2FskVOgsU6ZizcKvXjIIWhNJPYri9x0J%2BY9ex6C0%3D&default_email=&order_id=192032 : 1. 3950000001 192032 2. . 3950000002 192032 . 3. . ! " order_id XXXXX. XXXXXXXXXX", "" , "" .
pay men t_ty pe	1. , 0, 2.0		<i>spg</i> <i>spg_test ()</i>
rec urre nt_t ype	1. , 0, 2.0 : • «first» - ; • «next» - ; • - .		= "first" : email, order_id, recurrent_comment, recurren t_url, recurrent_period = "next" : background=1, order_id, recurrent_order_id
rec urre nt_c om ment	1. 0, 2.0		. . .
rec urre nt_ url	1. 0, 2.0		: http://example.com/rules
rec urre nt_ peri od	1. 0, 2.0		: byrequest recurrent_type=first

check	2.0	2.0 – .. 1	version='2.0' service_id. key .
service_id	2.0	, 2.0	121233
version	2.0	. API, 1.0. API 1.0.	2.0
check ()	1.0	<i>MD5 : key + cost + name + email + order_id + comment + payment_type + recurrent_comment + recurrent_url + recurrent_type + recurrent_order_id + recurrent_period + secret_key</i>	() . secret_key (). .

, e-mail () .
 . **command=success : recurrent_order_id card . . .**

recurrent_order_id .

()

<https://partner.rficb.ru/alba/input/> :

	API		/
payment_type	1.0, 2.0	.	spg spg_test
recurrent_type	1.0, 2.0	"next", .	"next"
recurrent_order_id	1.0, 2.0	C order_id , order_id . 6-20 . recurrent_type=next	123456 (6)
background	1.0, 2.0	,	1
check	2.0	2.0 – .. 1	version='2.0' service_id. key .
service_id	2.0	, 2.0.	121233
version	2.0	. API, 1.0. API 1.0.	2.0
check ()	1.0	() <i>MD5 : key + cost + name + email + order_id + comment + payment_type + recurrent_comment + recurrent_url + recurrent_type + recurrent_order_id + recurrent_period + secret_key</i>	. <i>secret_key</i> ().

, . . . : **recurrent_order_id card . . .**

[background=1.](#)

()

URL: https://partner.rficb.ru/alba/recurrent_change/

	API		/
operation	1.0, 2.0	, "cancel"	
order_id	1.0, 2.0	order_id	
service_id	1.0, 2.0		
check	2.0	2.0 – .. 1	

version	2.0	. API, 1.0. API 1.0.	2.0
<i>()</i> check	1.0	<i>()</i> <i>MD5 : operation + service_id + order_id + secret_key. secret_key .</i>	

, **command=recurrent_cancel.**

, **command=recurrent_expire.**

. . .